

## RFID incoming and outgoing goods registration system

Gate Solution Extension package-sensors



### Application

|                        |                                                        |
|------------------------|--------------------------------------------------------|
| Design                 | extension package with retro-reflective laser sensor   |
| Radio approval for     | USA; Canada; Australia; Singapore; Malaysia; Indonesia |
| Note on radio approval | radio approval for the RFID evaluation unit DTE930     |

### Electrical data

|                   |     |            |
|-------------------|-----|------------|
| Operating voltage | [V] | 20...30 DC |
|-------------------|-----|------------|

### Mechanical data

|        |     |       |
|--------|-----|-------|
| Weight | [g] | 19230 |
|--------|-----|-------|



## RFID incoming and outgoing goods registration system

Gate Solution Extension package-sensors

| Accessories    |                                                                                                     |
|----------------|-----------------------------------------------------------------------------------------------------|
| Items supplied | RFID evaluation unit UHF: 1, DTE930                                                                 |
|                | RFID UHF antenna: 4, ANT960                                                                         |
|                | Connection cable: 4, E80332                                                                         |
|                | Ethernet switch: 1, AL3050                                                                          |
|                | IO-Link master: 1, AL1122                                                                           |
|                | Retro-reflective laser sensor: 2, OGP700                                                            |
|                | Reflector for retro-reflective laser sensors: 2, E20722                                             |
|                | 5-segment light tower: 1, DV2510                                                                    |
|                | Connection cable: 3, EVC108                                                                         |
|                | Power supply: 1, DN4012                                                                             |
|                | Connecting cable with socket: 4, EVC003                                                             |
|                | Connection cable: 3, E21137                                                                         |
|                | Adapter cable: 1, E80412                                                                            |
|                |                                                                                                     |
| Remarks        |                                                                                                     |
| Remarks        | Article is preprogrammed specifically for the Application Package.                                  |
|                | Dieser Artikel ist ein Ergänzungsset zu folgendem Artikel: ZZ0820, ZZ0818                           |
|                | Zur Verwendung dieses Sets wird ein Master Set mit folgender Artikelnummer benötigt: ZZ0820, ZZ0818 |
|                | maximum number of complementary sets on a master set: 9                                             |
|                | loading direction detection via retro-reflective sensors                                            |
| Pack quantity  | 1 pcs.                                                                                              |